

SAFETY DATA SHEET

KER 8240

1. IDENTIFICATION

A. Product name

- KER 8240 [MSDS-114]

B. Recommended use and restriction on use

- General use : EPOXY
- Restriction on use : -

C. Manufacturer / Supplier / Distributor information

• Manufacturer information

- Company name : KUMHO P&B CHEMICALS

- Address : Yeosu-sandan 2ro, Yeosu-city, Jeollanam-do, korea

- Dept. : Environment & Safety Team
 - Telephone number : 061-688-3682,061-688-3684

- Emergency telephone number : 061-688-3507 - Fax number : 061-688-3686

 $\circ \ Supplier/Distributer \ information$

- Company name : KUMHO P&B CHEMICALS

- Address : East Wing 8F, SignitureTowers Seoul, 100 Cheonggyecheon-ro, jung-gu, Seoul,

- Dept. : Epoxy Resin Business Team
- Telephone number : +82-2-6961-3464,3481
- Emergency telephone number : +82-2-6961-1114
- Fax number : 82-2-6961-3490,3492
- E-mail address : epoxy_domestic@kpb.co.kr

2. HAZARD IDENTIFICATION

A. GHS Classification

Flammable liquids: Category3
Acute toxicity (oral): Category4
Skin sensitization: Category1
Germ cell mutagenicity: Category2
Reproductive toxicity: Category2

Specific target organ toxicity(Single exposure): Category2
 Specific target organ toxicity(Repeated exposure): Category2

- Chronic aquatic toxicity : Category2

B. GHS label elements

o Hazard symbols









- o Signal words
 - Warning
- o Hazard statements
 - H226 Flammable liquid and vapour

- H302 Harmful if swallowed
- H317 May cause an allergic skin reaction
- H341 Suspected of causing genetic defects
- H361 Suspected of damaging fertility or the unborn child
- H371 May cause damage to organs (Refer Section SDS 11)
- H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- H411 Toxic to aquatic life with long lasting effects

o Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- $\hbox{- P241 Use explosion-proof electrical/ventilating/lighting/equipment.}\\$
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe gas/mist/vapours/spray.
- P261 Avoid breathing gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P309+P311 If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P330 Rinse mouth.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

\circ NFPA grade (0 ~ 4 level)

- Health: 2, Flammability: 2, Reactivity: 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)	l
---------------	--------------------------	---------	------------	---

2,2-Bis(4'-glycidyloxyphenyl)propane	Diphenylol propane dicylcidyl ether; Bisphenol A diglycidyl ether; Dimethylmethane diglycidyl ether; 2,2-bis(4-(2,3-Epoxypropoxy)phenyl) propane; 2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxira ne; 4,4'-Bis(2,3-epoxypropoxy)diphenyldimethyl methane; Bis(4-hydroxyphenyl)dimethylmethane diglycidyl ether; Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-; 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxira ne; Bisphenol A diglycidyl ether	1675-54-3	75
Phenol polymer with formaldehyde, glycidyl ether	-	28064-14-4	10
Benzyl alcohol	-	100-51-6	10
Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.	-	68609-97-2	5

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Wash thoroughly after handling.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Avoid inhalation of materials or combustion by-products.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- Due to the extremely low flash point, irrigating fire extinguishing may be less effective when put out a fire.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Must work against the wind, let the upwind people to evacuate.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- $Small\ leak:$ sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Dealing only with a well-ventilated place.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- Prevent static electricity and keep away from combustible materials or heat sources.
- Collected them in sealed containers.
- Do not eat, drink or smoke when using this product.
- Store away from water and sewer.

A. Exposure limits

- o ACGIH TLV
 - Not available
- OSHA PEL
 - Not available

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Individual protection measures, such as personal protective equipment

o Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

o Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

Hand protection

- Wear appropriate chemical resistant glove.

o Skin protection

- Wear appropriate chemical resistant protective clothing.

Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
11	I imid/Ilianous limid)
- Appearance	Liquid(Viscous liquid)
- Color	투명(옅은 노란색)
B. Odor	독특한 냄새
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	<-15 ℃
F. Initial Boiling Point/Boiling Ranges	$^{\circ}$
G. Flash point	93 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	13 - 1.3 vol%
K. Vapour pressure	13.2mmHg
L. Solubility	4.29g/100ml
M. Vapour density	3.7
N. Specific gravity(Relative density)	1.04
O. Partition coefficient of n-octanol/water	1.1
P. Autoignition temperature	436 ℃
Q. Decomposition temperature	Not available
R. Viscosity	0.7 ~ 1.1 Pa.s (at 25 °C)
S. Molecular weight	235~263

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- o (Respiratory tracts)
 - Not available
- o (Oral)
 - Harmful if swallowed
- o (Eye·Skin)
 - May cause an allergic skin reaction

B. Delayed and immediate effects and also chronic effects from short and long term exposure

o Acute toxicity

* Oral

- Product (ATEmix) : >5000mg/kg
- [2,2-Bis(4'-glycidyloxyphenyl)propane] : LD50 11,300 mg/kg rat (HSDB)
- [Phenol polymer with formaldehyde, glycidyl ether] : LD50 > 4000 mg/kg Rat (Dow Chemical)
- [Benzyl alcohol] : LD50 = 1230 mg/kg Rat (NITE)
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : LD50 = 17100 $\,\mathrm{mg/kg}$ Rat (Thomson)

* Dermal

- Product (ATEmix) : >5000mg/kg
- [2,2-Bis(4'-glycidyloxyphenyl)propane] : LD50 >23,200 $\rm mg/kg$ Rabbit (IARC, NITE)
- [Phenol polymer with formaldehyde, glycidyl ether] : LD50 = 6000 $\,\mathrm{mg/kg}$ Rabbit (Epoxylite)
- [Benzyl alcohol] : LD50 = 2000 mg/kg Rabbit (SIDS, NITE)

* Inhalation

- Product (ATEmix) : Not available
- [Benzyl alcohol] : LC50 = 6.25 mg/ ℓ 4 hr (1000ppm/8hr) Rat (HSDB)

O Skin corrosion/irritation

- Not available

$\circ \ Serious \ eye \ damage/irritation$

- Not available

$\circ \ Respiratory \ sensitization$

- Not available

o Skin sensitization

- May cause an allergic skin reaction

$\circ \ Carcinogenicity$

* IARC

- [2,2-Bis(4'-glycidyloxyphenyl)propane] : Group ${\bf 3}$

* OSHA

- Not available

* ACGIH

- Not available

* NTP

- Not available

* EU CLP

- Not available

o Germ cell mutagenicity

- Suspected of causing genetic defects

o Reproductive toxicity

- Suspected of damaging fertility or the unborn child

o STOT-single exposure

- May cause damage to organs

o STOT-repeated exposure

- May cause damage to organs through prolonged or repeated exposure

o Aspiration hazard

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

o Fish

- [Benzyl alcohol]: LC50 460mg/L 96hr fathead minnow (NITE: SIDS, 2004)
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : LC50 0.002 mg/ ℓ 96 hr (Estimate)

o Crustaceans

- [Benzyl alcohol] : EC50 230mg/L 48hr Daphnia magna (NITE: Ministry of the Environment, 1997)
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.]: LC50 0.003 mg/ ℓ 48 hr (Estimate)

o Algae

- [Benzyl alcohol] : EC50 770mg/L 72hr (NITE: Ministry of the Environment, 1997)
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : EC50 0.003 mg/ℓ 96 hr (Estimate)

B. Persistence and degradability

o Persistence

- [Benzyl alcohol] : log Kow = 1.1
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : log Kow 7.25 (Estimate)

o Degradability

- Not available

C. Bioaccumulative potential

- $\circ \ Bioaccumulative \ potential \\$
 - [Phenol polymer with formaldehyde, glycidyl ether] : BCF = 3.40 (Estimate)
 - [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.]: BCF 934.9 (Estimate)

$\circ \ Biodegration$

- [Benzyl alcohol] : Biodegradability = 94 (%) 28 day (Aerobic, Activated Sludge)

D. Mobility in soil

- [Phenol polymer with formaldehyde, glycidyl ether]: Koc = 4365.16 (log = 3.64 (Estimated from water solubility))
- [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : Koc = 12830

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Will be pre-processed by the separation of oil and water.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

A. UN No. (IMDG CODE/IATA DGR)

- 3082

B. Proper shipping name

- ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (2,2-Bis(4'-glycidyloxyphenyl)propane)

C. Hazard Class

- 9

D. IMDG CODE/IATA DGR Packing group

- Ⅲ

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-F (Water-soluble marine pollutants)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

- o POPs Management Law
 - Not applicable
- o Information of EU Classification
 - * Classification
 - [2,2-Bis(4'-glycidyloxyphenyl)propane]: H319, H315, H317
 - [Benzyl alcohol] : H332, H302
 - [Oxirane, mono[(alkyl(C=12-14)oxy)methyl] derivs.] : H315, H317
- **Output** U.S. Federal regulations
 - * OSHA PROCESS SAFETY (29CFR1910.119)
 - Not applicable
 - * CERCLA Section 103 (40CFR302.4)
 - Not applicable
 - * EPCRA Section 302 (40CFR355.30)
 - Not applicable
 - * EPCRA Section 304 (40CFR355.40)
 - Not applicable
 - * EPCRA Section 313 (40CFR372.65)
 - Not applicable
- ${\small \circ}\ \textbf{Rotterdam}\ \textbf{Convention}\ \textbf{listed}\ \textbf{ingredients}\\$
 - Not applicable
- ${\color{gray} \circ} \ \textbf{Stockholm} \ \textbf{Convention listed ingredients}$
 - Not applicable
- o Montreal Protocol listed ingredients
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-09-12

C. Revision number and Last date revised

- 2 times, 2018-07-17

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).